

## YWF AXIAL FAN TECHNICAL DATA

MODEL	BLADE SIZE mm	DIRECTION	POLES	VOLTAGE v	FREQUENCY Hz	CURRENT Amps	INPUT Watts	CAPACITANCE µf	SPEED	AIR VOLUME	NOISE Dba	NET WEIGHT Kg	MOUNTS mm	BOLT HOLE mm
YWF-4E-200-S-G	200	INDUCED	4	240	50	0.21	40	1.5	1400	530	45	2	260	7
YWF-4E-250-S-G	250	INDUCED	4	240	50	0.23	50	2	1380	730	55	2.5	320	7
YWF-4E-250-B-G	250	FORCED	4	240	50	0.23	50	2	1380	730	55	2.5	320	7
YWF-4E-300-S-G	300	INDUCED	4	240	50	0.42	85	3	1350	1664	58	3	360	7
YWF-4E-300-B-G	300	FORCED	4	240	50	0.42	85	3	1350	1664	58	3	360	7
YWF-4D-300-S-G	300	INDUCED	4	415	50	0.22	75	N/A	1380	1563	58	3	360	7
YWF-4E-350-S-G	350	INDUCED	4	240	50	0.65	140	4	1380	2270	62	5	422	9.5
YWF-4E-350-B-G	350	FORCED	4	240	50	0.65	140	4	1380	2270	62	5	422	9.5
YWF-4D-350-S-G	350	INDUCED	4	415	50	0.38	140	N/A	1380	2290	62	5	422	9.5
YWF-4E-400-S-G	400	INDUCED	4	240	50	0.82	180	6	1380	3541	68	6	470	9.5
YWF-4D-400-S-G	400	INDUCED	4	415	50	0.47	180	N/A	1380	3400	68	6	470	9.5
YWF-4E-450-S-G	450	INDUCED	4	240	50	0.6	250	8	1350	4620	68	8	522	9.5
YWF-4D-450-S-G	450	INDUCED	4	415	50	1.2	250	N/A	1360	4800	68	8	522	9.5
YWF-6E-450-S-G	450	INDUCED	6	240	50	0.75	150	6	920	3220	60	8	522	9.5
YWF-6D-450-S-G	450	INDUCED	6	415	50	0.42	150	N/A	900	3520	60	8	522	9.5
YWF-4E-500-S-G	500	INDUCED	4	240	50	1.95	420	10	1300	6420	72	9	570	10.5
YWF-4D-500-S-G	500	INDUCED	4	415	50	0.9	450	N/A	1300	6570	72	9	570	10.5
YWF-4D-500-S-B	500	INDUCED	4	415	50	0.9	450	N/A	1300	6570	72	9	570	10.5
YWF-6D-500-S-G	500	INDUCED	6	415	50	0.55	230	N/A	900	4840	68	9	570	10.5
YWF-4E-550-S-G	550	INDUCED	4	240	50	2.55	550	12	1300	8010	75	11	622	10.5
YWF-4D-550-S-G	550	INDUCED	4	415	50	1.2	600	N/A	1300	8720	75	11	622	10.5
YWF-4D-550-S-B	550	INDUCED	4	415	50	1.2	600	N/A	1300	8720	75	11	622	10.5
YWF-6D-550-S-G	550	INDUCED	6	240	50	0.9	330	N/A	900	6430	70	11	622	10.5
YWF-4E-630-S-G	630	INDUCED	4	240	50	3.5	750	16	1360	10860	78	15	750	10.5
YWF-4D-630-S-G	630	INDUCED	4	415	50	1.6	800	N/A	1320	12200	78	15	750	10.5
YWF-6D-630-S-G	630	INDUCED	6	415	50	1.45	550	N/A	900	8830	75	15	750	10.5
YWF-4D-630-S-B	630	INDUCED	4	415	50	1.6	800	N/A	1320	12200	75	15	750	10.5

OTHER MODELS ARE AVAILABLE BY SPECIAL ORDER